



ANACONDA / PACKLESS

Metallschläuche | Metal hoses

Ausführung Version	Typ Type	Gesamtlänge Length o. a. L [± 6 mm]	Innen-Lötanschluss Connection size ODS		P _{smax} bar
			ØD [mm]	ØD [inch]	
1. ANACONDA BRONZE	M6FX [REST]	190	6	1/4	28
	M8FX [REST]	210	10	-	28
	M10FX [REST]	229	12	-	28
	M13FX [REST]	248	15	-	28
	1212FY [REST]	248	16	5/8	28
	M13AFX [REST]	254	18	-	28
	1258FX [REST]	254	-	3/4	28
	3434FX [REST]	292	22	7/8	28
	1010FY [REST]	330	28	1-1/8	28
5454FX [REST]	375	35	1-3/8	28	
2. ANACONDA STAINLESS STEEL	M38FS [REST]	432	42	1-5/8	28
	2020FS [REST]	508	54	2-1/8	24
	5252FS [REST]	610	67	2-5/8	25
	M64FS20* [REST]	508	64	2-1/2	25
	M76FSH [REST]	686	76	3	25
	3030FSH [REST]	686	80	3-1/8	25
	M89FSH [REST]	686	89	3-1/8	25
	M104FS [REST]	584	104	4-1/8	16
	M108/4040FSH [REST]	635	108/104	4-1/4	16
3. PACKLESS REDBRASS	VAF-3 [REST]	210	-	3/8	34
	VAF-5 [REST]	248	16	5/8	34
	VAF-7 [REST]	286	-	3/4	34
	VAF-9 [REST]	330	28	1-1/8	34
	VAF-11 [REST]	432	42	1-5/8	34
4. PACKLESS STAINLESS STEEL	VAF-82 [REST]	508	54	2-1/8	26
	VAF-83 [REST]	610	67	2-5/8	23
	P-76 [REST]	686	76	3	20
	VAF-84 [REST]	686	80	3-1/8	20
	VAF-86 [REST]	584	104	4-1/8	12
	P-108* [REST]	635	108/104	4-1/4	12

* Beidseitig mit Stahladapter / Both sides equipped with steel adapters



VAFS Vibrationsdämpfer (bis 60 bar) | Vibration eliminators (up to 60 bar)

Ausführung Version	Typ Type	Gesamtlänge Length o. a. L [± 5 mm]	Innen-Lötanschluss Connection size ODS		P _{max} bar	R 410A	R 744	R 290	R 600a	R 717	R 723	R 1270
			ØD [mm]	ØD [inch]								
1. EDELSTAHL * 1. STAINLESS STEEL *	VAFS-31	210	-	3/8	60	●	●	●	●	-	-	●
	PS-10	210	10	-	60	●	●	●	●	-	-	●
	PS-12	230	12	-	60	●	●	●	●	-	-	●
	VAFS-41	230	-	1/2	60	●	●	●	●	-	-	●
	VAFS-51	248	16	5/8	60	●	●	●	●	-	-	●
	VAFS-81	292	22	7/8	60	●	●	●	●	-	-	●
	VAFS-91	330	28	1-1/8	60	●	●	●	●	-	-	●
	VAFS-101	375	35	1-3/8	60	●	●	●	●	-	-	●
	VAFS-11	432	42	1-5/8	45	●	●	●	●	-	-	●

* Anschlüsse: Kupfer / Connections: Copper

ANACONDA / PACKLESS Wärmetauscher | Heat exchanger

Hersteller Manufacturer	Typ Type	Gesamtlänge Length o. a. L [mm]	Innen-Lötanschluss Connection size ODS		P _{max} bar
			ØFL [inch]	ØSL [inch]	
2. ANACONDA	AHX-10 058 [REST]	350	3/8	5/8	28
	AHX-00 078 [REST]	368	3/8	7/8	28
	AHX-00 118 [REST]	380	3/8	1.1/8	28
	AHX-10 118 [REST]	380	1/2	1.1/8	28
	AHX-00 138 [REST]	368	5/8	1.3/8	28
	AHX-00 158 [REST]	432	5/8	1.5/8	28
	AHX-00 218 [REST]	460	7/8	2.1/8	28
3. PACKLESS	HXR-50	350	3/8	5/8	31
	HXR-75	368	3/8	7/8	31
	HXR-100	359	3/8	1.1/8	31
	HXR-150	359	1/2	1.1/8	31
	HXR-250A	368	5/8	1.3/8	27
	HXR-350A	432	5/8	1.5/8	27
	HXR-500	460	7/8	2.1/8	23